

## ALLORA® KITCHEN COLLECTION WITH EZ ANCHOR™ MOUNTING



Installation is easier than ever with the EZ Anchor mounting assembly.

- Secure faucet from above, no need to go below deck
- Mounts faucet tightly to deck, no loosening over time
- Installs on up to 2-1/2"-thick decks, like granite or quartz



SINGLE-HANDLE PULL-DOWN  
989-AR-DST  
*1 or 3-hole installation*



SINGLE-HANDLE PULL-DOWN  
989-AR-DST WITH  
RP47280AR SOAP DISPENSER  
*2 or 4-hole installation*



SINGLE-HANDLE PULL-DOWN  
BAR/PREP  
999-AR-DST  
*1 or 3-hole installation*



Chrome



Arctic™  
Stainless  
AR

Products shown in Arctic™ Stainless.

**EZ** = EZ Anchor™ Mounting



= Water-Efficient Product  
Kitchen Faucets: flow rate of 1.5 gpm or 1.8 gpm  
versus Industry Standard ASME A112.18.1/CSA  
B125.1 of 2.2 gpm. Meets CALGreen standards.



= DIAMOND™ Seal Technology



= CAVT Compliant

# EZ ANCHOR™ INSTALLATION



## Step 1

Insert the EZ Anchor mounting assembly through the hole in the countertop.

## Step 2

Tighten the screw to adjust the first cleat (black wedge that secures the assembly beneath the deck) until it's flush with the bottom of the deck. Repeat for the second cleat.

## Step 3

Place the spout hub through the assembly, aligning the cut-out and handle. Ensure the small tube is in front of the supply lines.

## Step 4

Slide the spout hub install rod (EZ Bar), through the two holes on the spout hub and rotate clockwise until tightened.

## Step 5

Slide the spout down over the spout hub.

## Step 6

Install the wand and then connect the water supplies.



see what Delta can do™

deltafaucet.com  
800.345.DELTA (3358)  
©2011 Masco Corporation of Indiana  
DL-1742 11/11